

## United States Patent [19]

Yablon

[11] Patent Number: 5,764,731

[45] Date of Patent: Jun. 9, 1998

[54] **ENHANCED SYSTEM FOR TRANSFERRING, STORING AND USING SIGNALING INFORMATION IN A SWITCHED TELEPHONE NETWORK**

5,148,473 9/1992 Freedland et al. .... 379/59  
5,168,517 12/1992 Waldman ..... 379/67  
5,212,721 5/1993 DeLuca et al. .... 379/57

(List continued on next page.)

[76] Inventor: Jay R. Yablon, 910 Northumberland Dr., Schenectady, N.Y. 12309-2814

[21] Appl. No.: 378,529

[22] Filed: Jan. 26, 1995

## Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 322,209, Oct. 13, 1994, abandoned.

[51] Int. Cl.<sup>5</sup> ..... H04M 1/27; H04M 3/52  
[52] U.S. Cl. .... 379/88; 379/93.18; 379/93.23;  
379/93.26; 379/216; 379/213; 379/355  
[58] Field of Search ..... 379/216, 354,  
379/355, 213, 97, 217, 201, 207, 142, 210,  
211, 212, 67, 88, 89, 58, 59, 202, 205,  
206, 203, 204, 93.18, 93.23, 93.26, 69,  
57

## [56] References Cited

## U.S. PATENT DOCUMENTS

4,053,949	10/1977	Recca et al.	379/213
4,644,107	2/1987	Cloves et al.	379/354
4,724,539	2/1988	Hiskes	379/205
4,800,582	1/1989	D'Agostino, III et al.	379/355
4,839,919	6/1989	Borges et al.	379/96
4,832,146	7/1989	Hathcock et al.	379/58
4,924,496	5/1990	Figa et al.	379/142
4,926,461	5/1990	Kouk	379/212
4,933,968	6/1990	Iggulden	379/216
4,941,168	7/1990	Kelly, Jr.	379/69
4,942,598	7/1990	Davis	379/57
4,945,557	7/1990	Kasowitz et al.	379/67
4,979,206	12/1990	Padden et al.	379/67
5,075,894	12/1991	Iwase et al.	379/69
5,097,502	3/1992	Suzuki et al.	379/358
5,127,040	6/1992	D'Avolio et al.	379/58

## OTHER PUBLICATIONS

IBM Technical Disclosure Bulletin, "Mechanism to Automate Updating of Obsolete Telephone Numbers", vol. 37, No. 04A, pp. 115-116, Apr. 1994.

Primary Examiner—Krista Zele  
Assistant Examiner—Daniel S. Hunter  
Attorney, Agent, or Firm—Jay R. Yablon

## [57] ABSTRACT

A system includes a telephone and a distant device. The distant device contains one or more telephone numbers which are later to be dialed at the telephone. The telephone numbers are transmitted in coded form, preferably dual tone multifrequency form, from the device to the telephone. The distant device may be a directory assistance service position, a caller ID receiver, and answering machine, a voice or electronic mail system, a terminal operated by a secretary or receptionist, or a simple DTMF keyboard. After the telephone numbers are received, they are stored in any of several memories in the telephone. Later, the user selects one of the entries for dialing and the entry is used for address signaling. Optionally, storage, selection and dialing of a memory entry can be further simplified by using voice processing techniques. The system is particularly pertinent to the driver of an automobile who is operating a cellular telephone, to a travelling individual who regularly receives and needs to return a large number of calls, to a pedestrian carrying a portable telephone, or to a person with a physical disability, because it saves the user having to jot down telephone numbers and dialing them manually. A particularly significant embodiment enables the user of this system to establish a customized paging service through an ordinary telephone network, using end-user, customer premises equipment only.

13 Claims, 19 Drawing Sheets

